



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
AEP-251

19059671

30/04/2021

DENOMINATION:


Professional display refrigerated cabinet with 2 shelves.

DESCRIPTION :

Professional display refrigerated cabinet:

- Steel sheet exterior with white epoxy coating that provides high resistance to impacts and daily use.
- Inner body in food-standard ABS material.
- Interior corners and edges rounded to facilitate cleaning.
- Equipped with inner fluorescent lighting to help display and draw attention to your products.
- Double glazed door with handle incorporated into the frame
- Reversible door with frame manufactured in aluminium, providing it with an elegant and very aesthetically pleasing finish.
- Equipped with lock and key as standard.
- Digital thermometer with temperature control.
- Operational voltage: 230 V - 50 Hz.
- Guides inbuilt into the sides of the cabinet with anti-tip system.
- Drain inside the chamber.
- Forced refrigeration. Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
- R-600a hydrocarbon refrigerant gas.
- Operational temperature: -1 °C ÷ +6 °C, Ambient temperature 32 °C.

DIMENSIONS



X Width	626 mm	X Gross width	715 mm
Y Depth	600 mm	Y Gross depth	647 mm
Z Height	850 mm	Z Gross height	975 mm
Net Weight	53,0 kg	Gross Weight	55,0 kg
Net volume	0,391 m3	Gross volume	0,451 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,091 kW
Amperage (A)	0,72A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,140 kW
Climate class	4
Cooling gas load	29,000 g

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

OTHERS

Condensation system	Static
---------------------	--------



Catalogue
FOOD SERVICE

Capítulo
REFRIGERATION

Modelo
AEP-251

19059671

30/04/2021

