



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
EAEP-701 CR 230V 1N 50Hz

19037072

30/04/2021

DENOMINATION:

Refrigerated display cabinet - Concept Snack with 1 door, at 50Hz.

DESCRIPTION :

- Constructed with AISI-304 stainless steel.
 - 50 mm, 40 kg/m³ injected polyurethane insulation.
 - Removable and height adjustable plasticcovered steel shelves (17 Snack size levels) for easy cleaning. Equipment: 3 shelves per large door.
 - Forced draught cooling system.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Ambient temperature: 43 °C (AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.)
 - Climatic class 4.
 - Inner LED lights with power switch (in refrigerated display cabinets and now also in freezing units).
- Freezer cabinet.
 Visibility: vertical LED light for greater visibility.

POSSIBLE OPTIONS :

- Opposite Opening
- Butcher Bar
- Wheels Kit (Factory Assembly)
- Stainless Backing
- Door frame resistance

STANDARD OPTIONS :

- Locks

POSSIBLE ACCESSORIES :

- REFRIGERATION

DIMENSIONS



X Width	693 mm	X Gross width	780 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	119,0 kg	Gross Weight	125,0 kg
Net volume	1,040 m ³	Gross volume	1,300 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,186 kW
Amperage (A)	0,81 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,361 kW
Gross internal volume	506 L
Climate class	4
Cooling gas load	92,000 g

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
Condensation system	Vent.



Catalogue
FOOD SERVICE

Capítulo
REFRIGERATION

Modelo
EAEP-701 CR 230V 1N 50Hz

19037072

30/04/2021

