



700 Series

Tilting bratt pans 700

ELECTRIC TILTING BRATT PAN, SBE7-10 I

1121134000

DIMENSION Length Depth Height Volume ELECTRICI Electric pow Voltage 230 Voltage 230 Voltage 400 PLUMBING	mm mm Kg m3 I TY //er IV -1+N IV - 1II IV - III+N	Article 700.00 780.00 850.00 114.00 0.46 KW	Packed 745.00 925.00 1,070.00 149.00 0.74 9.00 NO NO 00V-3+N+E	Made Pan ca Surfac Stainle Count Shield Pilot li Therm Manua Water Power Dimer *Supp 900m	of stainless ste apacity: 50 litre es area: 42 dm2 ess steel pan, v erweighted folc ed elements co ghts. nostat temperat al tillt system. feed by electro : 9 kW. Isions: 700 x 78 lied on height a	s (approx.). 2 with heat diffuser botto ling lid. ontrolled by thermosta cure control (50 °C to 3 ovalve. 30 x 850* mm. adjustable legs; total h	om 10 mm. thick. at. 315 °C).	350mm to
GAS Not used						D WITH POWER CO STALLED BY A QUA		NN.
STEAM Not used AIR Not used								
Connectior ELECTRICI COLD WAT	TY	X 500 350		2 150 105	Diameter 3/4"	Information		, AZ